PAPER • OPEN ACCESS

The Effect of Temperature to CTAB-assisted Solvothermal Synthesis of ${\rm TiO_2}$

To cite this article: N S Anwari et al 2019 IOP Conf. Ser.: Mater. Sci. Eng. 546 042003

View the article online for updates and enhancements.



IOP ebooks™

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

The Effect of Temperature to CTAB-assisted Solvothermal Synthesis of TiO₂

N S Anwari^{1*}, N Aini¹, A Hardian², V Suendo^{3,4} and A Prasetyo¹

¹Department of Chemistry, Faculty of Science and Technology, Universitas Islam Negeri Maulana Malik Ibrahim, Indonesia

²Department of Chemistry, Faculty of Science and Informatics, Jenderal Achmad Yani University, Indonesi

³Inorganic and Physical Chemistry Research Group, Faculty Mathematics and Natural Science, Indonesia

⁴Research Center for Nanoscience and Nanotechnology, Institut Teknologi Bandung, Indonesia

*Corresponding author: Nuraini.kkfamaliki@gmail.com

Abstract. Surface area has significant impact on the photocatalytic activity of semiconductor material. It was found that templates as structure directing agent played a role in regulating the surface area of materials. The most widely used as template is cetyltrimethylammonium bromide (CTAB) surfactant. In this research, TiO₂ was prepared by solvothermal method used temperature variations of 150, 175, 200, and 225 °C. The X-ray powder diffraction (XRD) data indicated that anatase phase of TiO₂ was successfully obtained with *I*4₁/amd space group and as the synthesis temperature was increased, the crystallinity increases. The spectra infrared spectroscopy (IR) showed the broad peak situated at wavenumber 400-800 cm⁻¹ which was assigned to the stretching Ti-O vibration. Raman spectra showed peaks at wavenumber 145, 197, 397, 516, and 639 cm⁻¹ which were attributed to vibration modes of anatase. The scanning electron microscopy (SEM) image demonstrated the morphology particle has homogeneous distribution and irregular shape. Furthermore, Brunauer-Emmett-Teller (BET) specific surface area showed the CTAB-assisted TiO₂ which was synthesized at 175 °C has the highest surface area of 227.043 m²/g in this research among the others.

Keywords: TiO2, solvothermal, CTAB, surface area

1. Introduction

Titanium dioxide (TiO₂) is an attractive semiconductor with widely advantages in various field due to its good chemical stability, economical cost, stable to light, non-toxic, chemically and biologically inert, thermodynamically stable, and high oxidizing ability [1-3]. As result, TiO₂ has broad applications such as photocatalyst, solar energy conversion, pigment, cosmetics, and medical applications [4-5]. TiO₂ semiconductor has three polymorphic crystal: anatase (tetragonal), rutile (tetragonal), and brookite (orthorhombic). The rutile phase is the most stable phase and anatase phase usually exhibit the highest photocatalytic activity [6-7]. Surface area influences the photocatalytic activity of material, as the surface area is increasing the active site will increase, thus causing high rate degradation of organic materials [8]. The Previous researcher reported that TiO₂ has low surface area,

Published under licence by IOP Publishing Ltd

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

those are 53, 15, 10, and 98.2 m²/g for commercial TiO₂ degussa P25, TiO₂ Aldrich, TiO₂ Aldrich anatase, and pure TiO₂ nanopowder, respectively [9]. Thus, TiO₂ needs a modification to increase the surface area.

Template material is a structure directing agent to strike pores with the result is increasing the surface area [10-11]. Generally, templates are categorized into two groups of soft and hard templates. The common hard templates are polymer microspheres, carbon fiber, and anodic aluminium oxide (AAO), while soft templates are surfactant, polymer, and biopolymer. Nevertheless, the hard template has deficiency which is the elimination of template may lead to the collapse of material pore structure. On the other hand, the soft template is easier to remove than the hard template and the most widely used of soft template is surfactant [12-13]. Wei et al. [14] reported that synthesis TiO₂ with assistance cetyltrimethylammonium bromide surfactants, such as (CTAB), dodecylbenzensulfonate (SDBS), and diethanolamine (DEA) could increase the surface area of TiO₂. The surface area of TiO₂-nonmodified, TiO₂-CTAB, TiO₂-SDBS, and TiO₂-DEA were 49.09, 83.45, 67.64, and 76.31 m²/g, respectively. The result showed that CTAB had the highest surface area than the other surfactants. Besides, it is well known that CTAB has capability to reduce the particle size and agglomeration of TiO₂ and improve the dispersion of TiO₂ [14-15].

It is well known that solvothermal has been widely applied in synthesis various materials such as metals, semiconductors, ceramics, and polymers. The solvothermal method is heterogeneous chemical reaction in isolated system with temperature presence above the boiling temperature of solvent used. The Solvothermal method has many advantages such as using low temperature, controllable particle size distribution and morphology [16-17], high homogeneity and purity, and improving crystallinity of TiO₂ [18]. There are many factors which are influencing the solvothermal synthesis such as temperature, experiment time, solvent type, precursor, and pH [19]. Wahi et al. [20] reported synthesis anatase TiO₂ using solvothermal method with temperature variations of 140-335 °C could decrease the surface area because the average grain size increased with increasing temperature. The increasing grain size occurred via Ostwald ripening, the process leads to dissolution of smaller grain size then diffusion of solute through liquid and reprecipitation into larger grain. TiO₂ material at temperature 140 °C had the highest surface area of 250.6 m²/g, otherwise at temperature 330 °C had the lowest surface area of 55 m²/g. Therefore, in this work, we investigated the effect of temperature to structure phase, morphology, and surface area of CTAB-assisted TiO₂ which was synthesized by solvothermal method.

2. Experimental Section

2.1. Materials

Titanium isopropoxide (TTIP) (Sigma –Aldrich 97%), cetyltrimethylammonium bromide (CTAB) [CH₃(CH₂)₁₅N(Br)(CH₃)] 1 mM, isopropyl alcohol *p.a*, and aquades.

2.2. Catalyst preparations

Material TiO₂ was prepared via solvothermal process with target yield about 2.5 g. Briefly, 0.0182 g of CTAB was added to 50 mL of isopropyl alcohol solvent and stirred for 30 minutes, vigorously. Next, 10 mL of TTIP was added drop by drop to the mixture solution under stirring condition. Acetic acid was added to the mixture until pH 1 and then sonicated for 5 minutes at room temperature. After sonication process, the as-prepared mixture transferred to a 100 mL teflon-lined stainless steel autoclave, sealed, and then heated at temperature variations of 150, 175, 200, and 225°C for 12 hours. After cooling at room temperature, the white precipitates were washed with isopropyl alcohol for 2-3 times, then dried at 100 °C for 12 hours.

2.3. Characterizations

The characteristic structure of sample was studied by XRD Philip E'xpert Pro at range $2\theta = 20-80^{\circ}$. The XRD data were refined using Le Bail Method at Rietica program. The infrared vibration modes of

sample were measured using Varian 1000 FT-IR at spectral range 400-4000 cm⁻¹. The Raman vibration modes of sample was measured using Bruker-Senterra Spectrometer at spectral range 50-3600 cm⁻¹ and using laser excitation source of 532 nm. The surface morphology of sample was observed using SEM-EDX FEI, Type: Inspect-S50. The specific surface area was estimated by BET surface area NOVA 1200e, Quantachrome.

3. Results and discussions

Figure 1 showed the X-ray diffractions pattern of CTAB-assisted TiO_2 and can be seen that all the diffraction peaks were good agreement with pure anatase TiO_2 (ICSD 9852 with space group $I4_1/amd$). There was no other peak of any impurities or precursors residual. Furthermore, as the solvothermal temperature increased the intensity of XRD diffractions increased, which was indicating that the crystallinity of TiO_2 was increasing [19, 21]. It indicated that heat treatment had ability to remove organic impurities within TiO_2 and to promote crystallinity [22]. The results of refinement were showed in Figure 2 and the crystallographic data were summarised in Table 1. The result concluded that the lattice parameters were not different significantly, but the lowest value was obtained by CTAB-assisted TiO_2 with temperature 175 °C. Furthermore, the agreement between sample and standart was referred to the pattern factor (Rp), the weighted pattern factor (Rwp), and the goodness of fit (GoF) value (Table 2). Eddya, et al. [23] reported that the reliable value for both Rp and Rwp were under 15%, while the GoF was near or less than 2.




Figure 1. X-ray diffractions pattern of CTAB-assisted TiO₂ at temperature (a) 150, (b) 175, (c) 200, and (d) 225 °C synthesized by solvothermal.

The XRD pattern were used to calculate the crystallite size of CTAB-assisted TiO₂ materials using Debye-Scherrer equation (equation 1) [11].

$$S_{hkl} = \frac{K\lambda}{B\cos\theta} \tag{1}$$

 S_{hkl} is the average crystallite size for hkl peak in Angstrom (Å), K is the Scherrer constant (0.89), λ is the X-ray wavelength for Cu-K α_1 radiation (1.5406 Å), θ is the diffracted angle at maximum intensity,

and B is the Full Width at Half Maximum (FWHM) in radians. The crystallite size of materials were summarised in Table 2 and showed that CTAB-assisted TiO₂ with temperature 200 °C had the largest crystallite size in this research.




Figure 2. Refinement result of CTAB-assisted TiO₂ obtained in different synthesis temperatures.

Table 1. Crystallographic data of CTAB-assisted TiO₂ with different synthesis temperature

Materials	a=b (Å)	c (Å)	Rp (%)	Rwp (%)	GoF
TiO ₂ -CTAB 150 °C	3.890(4)	9.769(5)	14.70	13.88	0.04
TiO ₂ -CTAB 175 °C	3.786(2)	9.484(9)	12.30	8.93	0.49
TiO ₂ -CTAB 200 °C	3.7888(5)	9.488(1)	14.04	9.92	0.03
TiO ₂ -CTAB 225 °C	3.7902(4)	9.494(1)	13.95	9.84	0.03

Table 2. Crystallite size of CTAB-assisted TiO₂ obtained in different synthesis temperature.

Materials	Crystallite size (nm)		
TiO ₂ -CTAB 150 °C	14.40		
TiO ₂ -CTAB 175 °C	58.74		
TiO ₂ -CTAB 200 °C	78.15		
TiO ₂ -CTAB 225 °C	23.42		

The IR spectra of sample were showed in Figure 3. The band in range 400-800 cm⁻¹ was assigned to vibration mode of Ti-O bonds in crystalline anatase phase [24-27]. The impurities bands were identified, the absorption peaks at 3404 and 1635 cm⁻¹ were attributed to hydroxyl functional group of absorbed water and Ti-OH, respectively [14, 25]. The bands at 1536 and 904 cm⁻¹ were the characteristics bands of CTAB, while the bands at 1442 and 1340 cm⁻¹ were C-H stretching and C-H bending of CTAB [28], and band at 1026 cm⁻¹ was C-O bending of acetic acid [29]. The spectra showed that the impurities peaks were decreasing with increasing solvothermal temperature, which was indicating that impurities functional group were diminished in the materials [21].




Figure 3. IR spectra of CTAB-assisted TiO₂ synthesized by solvothermal with temperature variations.




Figure 4. Raman spectra of CTAB-assisted TiO₂ synthesized by solvothermal with temperature variations.




Figure 5. Raman spectra of CTAB-assisted TiO₂ at wavenumbers 800-3200 cm⁻¹ synthesized by solvothermal with temperature variations.

Figure 4 showed the Raman vibration of TiO_2 and found the five Raman active modes at 145, 197, 397, 516, and 639 cm⁻¹ which were assigned to E_g , B_{Ig} , A_{Ig} , E_g , and E_g , respectively [30-31]. The observed peaks at spectral range of 800-3200 cm⁻¹ related to the impurities peaks of precursors residual which was depicted in Figure 5. The peaks at 950 and 1441 cm⁻¹ were correspond to CH₂ rocking mode and bending of CTAB [32-33], while peaks at 1556 and 2941 cm⁻¹ were correspond to C=N and CH₃ from $-N^+(CH_3)_3$ symmetric stretching vibrations of CTAB [34]. The intensity of CTAB Raman vibration mode decreased at synthesis temperature of 200 and 225 °C which were indicating that the concentration of CTAB in samples decreased. The decreasing in intensity occurred because CTAB evaporated at higher synthesis temperature.

Table 3. BET surface area of CTAB-assisted TiO₂ synthesized by solvothermal with temperature variations.

Materials	Surface area (m ² /g)		
TiO ₂ -CTAB 150 °C	132.892		
TiO ₂ -CTAB 175 °C	227.043		
TiO ₂ -CTAB 200 °C	60.104		
TiO ₂ -CTAB 225 °C	62.896		

The BET measurement results were summarised in Table 3 and showed that CTAB-assisted TiO₂ at 175 °C had the highest surface area. The high surface area could provide more active sites which is beneficial to the photocatalytic activity. Besides, the results also indicated that high temperature at 200 and 225 °C in solvothermal system could reduce the surface area. The low surface area could probably occur because of particle agglomeration through Ostwald ripening process. Researchers reported that agglomerated particle was undesirable because reduce the surface area [36-38].

The SEM images in Figure 6 showed that the shapes of CTAB-assisted TiO₂ materials were still irregular, but generally they were in spherical shape. Material CTAB-assisted TiO₂ at 175 °C has the most homogeneous surface distribution, while CTAB-assisted TiO₂ at 200 °C and 225 °C were agglomerated. Agglomeration is a process of particles dispersed in liquid phase stick to each other and spontaneously forms irregular particle cluster or aggregate. Agglomeration occurred as the effect of high solvothermal temperature which were increasing the surface energy, so to minimize this energy the particles tend to agglomerate [35].




Figure 6. SEM images of CTAB-assisted TiO₂ at temperature (a) 150, (b) 175, (c) 200, and (d) 225 °C synthesized by solvothermal.

4. Conclusions

The anatase phase of TiO_2 was successfully prepared by solvothermal method using TTIP as titanium source and CTAB surfactant in isopropanol solvent. The surface area of TiO_2 was modified by assistance of CTAB surfactant and temperature variation during preparation. The highest surface area was obtained for the sample synthesized at 175 °C. However, further temperature at 200 and 225 °C caused an agglomeration of particles and consequently diminishing the surface area of CTAB-assisted TiO_2 material.

Acknowledgments

This project was financially supported by Penelitian Kompetitif Mahasiswa (PKM) Faculty Science and Technology, Universitas Islam Negeri Maulana Malik Ibrahim Malang2018.

References

- [1] Linsebigler A L, Lu G, and Yates J T 1995 Chem. Rev. **95** 735-758
- [2] Pookmanee P, Phiwchai I, Yoriya S, Puntharod R, Sangrichan S and Phanichphant S 2013

Ferroelectrics 457 30-38

- [3] Sayed M, Pingfeng F, Khan H M and Zhang P 2014 Int. J. Photoenergy 1-11
- [4] Lusvardi G, Barani C, Giubertoni F and Paganelli G 2017 Materials 10 1-11
- [5] Ge M, Cao C, Huang J, Li S, Chen Z, Zhang K Q, Al-Deyab S S and Lai Y 2016 *J. Mater. Chem. A.* **4** 6772–6801
- [6] Yang L, Wang C, Liu Z, Liu X, Song Y, Feng X and Zhang B 2017 Ceram. Int. 1-25
- [7] Pookmanee P, Phiwchai I, Yoriya S, Puntharod R, Sangsrichan S, Kittikul J and Phanichphant S 2015 *Mater. Sci. Forum* **804** 209–212
- [8] Wen J, Li X, Liu W, Fang Y, Xie J and Xu Y 2015 Chinese J. Catal. 36 2049–2070
- [9] Hussain M, Ceccarelli R, Marchisio D L, Fino D, Russo N and Geobaldo F 2010 *Chem. Eng. J.* **157** 45–51
- [10] Wu S H, Mou C Y and Lin H P 2013 Chem. Soc. Rev. 1-14
- [11] Marien C B D, Marchal C, Koch A, Robert D and Drogui P 2016 Environ. Sci. Pollut. Res. 1-7
- [12] Xie Y, Kocaefe D, Chen C and Kocaefe Y 2016 J. Nanomater. 1-10
- [13] Ramimoghadam D, Bagheri S and Hamid S B A 2014 BioMed. Res. Int. 1-7
- [14] Wei J, Wen X and Zhu F 2018 J. Nanomater. 1-7
- [15] Vishwanath A D, Shankar J S, Eknath N M, Eknath A A and Haribhau K N 2017 *Orient. J. Chem.* **33** 104-112
- [16] Canu G and Buscaglia V 2017 Cryst Eng Comm. 19 3867–3891
- [17] Wang Y, Sun J, Fan X and Yu X 2011 Ceram. Int. 37 3431–3436
- [18] Li J, Wu Q and Wu J 2015 Handbook of Nanopaticle 1-28
- [19] Khaksar E, Afarani M S and Samimi A 2016 J. Metall. Mater. Eng. 27 1-2
- [20] Wahi R K, Liu Y, Falkner J C and Colvin V L 2006 J. Colloid Interface Sci. 302 530-536
- [21] Perumal S 2015 Int. J. Eng. Res. Appl. 5 115–118
- [22] Othman S H, Rashid S A, Ghazi T I M and Abdullah N 2010 J. Nanomater. 1-11
- [23] Eddya M, Tbib B and El-Hami K 2018 J. Mater. Environ. Sci. 9 3087–3093
- [24] Sridevi D V, Ramesh V, Sakthivel T, Geetha K, Ratchagar V, Jagannathan K, Rajarajan K and Ramachadaran K 2017 Mechanics, *MMSE* 4-9
- [25] Wu W, Zhang L, Zhai X, Liang C and Yu K 2018 Nanomater. Nanotechno. 8 1-8
- [26] Ramalingam R J, Arunachalam P, Radhika T, Anju K R, Nimitha K C and al-Lohedan H A 2017 Int. J. Electrochem. Sci. 12 797–811
- [27] Gardy J, Hassanpour A, Lai X and Ahmed M H 2016 Applied Catal. A 527 81–95
- [28] Nithiyanantham U, Ramadoss A and Kundu S 2014 RSC Adv. 4 35659–35672,
- [29] Dong K, Choi J, Lee Y D, Kang B H, Yu Y, Choi H H and Ju B K 2013 Nanoscale. Res. Lett. 8
- [30] Syzrantsev V, Paukshtis E, Larina T, Chesalov Y, Bardakhanov S and Nomoev A 2018 *J. Nanomater.* 1-11
- [31] Ohsaka T, Izumi F and Fujiki Y 1978 J. Raman Spectrosc. 7 321–324
- [32] Foucault R, Birke R L and Lombardi J R 2003 Langmuir 19 8818–8827
- [33] Duan H, Jia L, Chen M, Ge S and Guo X 2016 Mater. Express 6 77–82
- [34] Joseph D, Rodriguez R D, Verma A, Pousaneh E, Zahn D R T, Lang H and Chandra S 2017 *RSC Adv.* 7 3628–3634
- [35] Liu X, Ye L, Liu S, Li Y and Ji X 2016 Sci. Rep. 1-9
- [36] Yunus N N, Hamzah F, So'aib M S and Krishnan J 2017 J. Mater. Sci. Eng. 206 1-7
- [37] Lin Y, Bai H, Lin C and Wu J 2013 Aerosol Air Qual. Res. 13 1512–1520
- [38] Sieland F, Schneider J and Bahnemann D W 2018 Phys. Chem. Chem. Phys. 20 8118-8132